

B275HA

HONDA GC160 2700 PSI





SPECIFICATIONS

| PART# | GPM | PSI | DISPLACEMENT | AXIAL PUMP | UNLOADER |
|---|---|---|-----------------------|---------------|----------|
| B275HA | 2.3 | 2700 | 160cc HONDA GC160 OHC | AR RMV 25G30D | BUILT-IN |
| | | | | | |
| ACCESSORIES INCLUDED | | | | | |
| PART # | DE | ESCRIPTION | | | |
| 85.225.228 | | 1/4" 25' HIGH PRESSURE STEEL BRAIDED HOSE | | | |
| 85.205.052 SPLIT WAND ASSEMBLY WITH GUN | | | | | |
| 85.210.030BE | 35.210.030BEP #3 QUICK CONNECT NOZZLES: 0°,15°, 40°, SDAPER | | | | |
| 85.309.124 | SF | PLIT LANCE, (| D-RING | | |

ADDITIONAL INFO

- LOW PRESSURE CHEMICAL INJECTOR
- POWDER COATED STEEL FRAME PART# 85.600.124
- 10" PNEUMATIC TIRES PART# 85.660.104
- ENGINE OIL 10W 30 PART# 85.490.002
- PUMP OIL 30W NON DETERGENT PART# 85.490.000
- 3/4" KEYED SHAFT
- THERMAL VALVE PART# 85.300.022

